

Specification of William Gilpin and Abraham Bowen : furnaces and ovens.

Contributors

Gilpin, William.
Bowen, Abraham.

Publication/Creation

London : Great Seal Printing Office, 1855 (London : George E. Eyre and William Spottiswoode)

Persistent URL

<https://wellcomecollection.org/works/y3sjsm5d>

License and attribution

This work has been identified as being free of known restrictions under copyright law, including all related and neighbouring rights and is being made available under the Creative Commons, Public Domain Mark.

You can copy, modify, distribute and perform the work, even for commercial purposes, without asking permission.



Wellcome Collection
183 Euston Road
London NW1 2BE UK
T +44 (0)20 7611 8722
E library@wellcomecollection.org
<https://wellcomecollection.org>



A.D. 1854 N° 2661.

SPECIFICATION

OF

WILLIAM GILPIN AND ABRAHAM BOWEN.

FURNACES AND OVENS.

LONDON:

PRINTED BY GEORGE E. EYRE AND WILLIAM SPOTTISWOODE,

PRINTERS TO THE QUEEN'S MOST EXCELLENT MAJESTY:

PUBLISHED AT THE GREAT SEAL PATENT OFFICE,

25, SOUTHAMPTON BUILDINGS, HOLBORN.

Price 3d.

1855.





A.D. 1854 N° 2661.

Furnaces and Ovens.

(This Invention did not proceed to the Great Seal.)

PROVISIONAL SPECIFICATION left by William Gilpin and Abraham Bowen at the Office of the Commissioners of Patents, with their Petition, on the 18th December 1854.

We, WILLIAM GILPIN, of No. 2, Moorgate Street, London, and ABRAHAM
5 BOWEN, of Stafford Street, Peckham, Engineers, do hereby declare the nature
of the said Invention for "**A NEW METHOD FOR THE EFFECTUAL CONSUMPTION
OR PREVENTION OF SMOKE & THE MORE PERFECT COMBUSTION OF COALS & OTHER
FUEL BY MEANS OF A MECHANICAL APPARATUS AND FURNACE BARS OF A CERTAIN
CONSTRUCTION; A PORTION OF THE SAME MAY BE APPLIED FOR RAISING WATER,
10 AND IN FURNACES WHERE BLAST IS REQUIRED,**" to be as follows, viz. :—

By means of angular bars placed in the door of the furnace, & which may
also be applied as grate bars, we prevent the radiation of heat from the furnace
or oven. A further improvement consists in affixing an extra door or slide to
the door already formed of angular bars, whereby the supply of air to the
15 furnace may be regulated. Also, by means of a machine constructed in the
form of a screw, and which we propose to term "the Archimedian fan
exhauster," we exhaust or draw from furnaces or sewers all smoke, gases,
or other volatile residuum.

LONDON:

Printed by GEORGE EDWARD EYRE and WILLIAM SPOTTISWOODE,
Printers to the Queen's most Excellent Majesty. 1855.

