Contributors

Descos, Aubin Emile Coullard.

Publication/Creation

London : Great Seal Patent Office, 1856 (London : George E. Eyre and William Spottiswoode)

Persistent URL

https://wellcomecollection.org/works/ab4npfc4

License and attribution

This work has been identified as being free of known restrictions under copyright law, including all related and neighbouring rights and is being made available under the Creative Commons, Public Domain Mark.

You can copy, modify, distribute and perform the work, even for commercial purposes, without asking permission.



Wellcome Collection 183 Euston Road London NW1 2BE UK T +44 (0)20 7611 8722 E library@wellcomecollection.org https://wellcomecollection.org



A.D. 1856 Nº 258.

SPECIFICATION

AUBIN EMILE COULLARD DESCOS.

OF

FIRE-PLACES, &c.

LONDON:

PRINTED BY GEORGE E. EYRE AND WILLIAM SPOTTISWOODE, PRINTERS TO THE QUEEN'S MOST EXCELLENT MAJESTY: PUBLISHED AT THE GREAT SEAL PATENT OFFICE, 25, SOUTHAMPTON BUILDINGS, HOLBORN.

1856.





A.D. 1856 Nº 258.

Fire-places, &c.

(This Invention received Provisional Protection, but notice to proceed with the application for Letters Patent was not given within the time prescribed by the Act.)

PROVISIONAL SPECIFICATION left by Aubin Emile Coullard Descos at the Office of the Commissioners of Patents, with his Petition, on the 31st January 1856.

I, AUBIN EMILE COULLARD DESCOS, of Paris, in the Empire of France, do hereby declare the nature of the said Invention for "IMPROVEMENTS IN CONSUMING SMOKE," to be as follows :---

5

10

15

The smoke-consuming hearth is composed of a chamber, having on its walls three openings; the first for charging the fuel, the second one on the adjacent wall for placing therein an horizontal twyer with a moveable inclination; this twyer extends on the whole dimension of the wall where it is inserted. The third one on the opposite wall of the twyer puts the chamber into communication with the flue by which the gaseous products escape. The chamber is divided at about half its height into two compartments by an almost horizontal grate. This grate does not take up the whole length of the chamber, & leaves room for a passage, beneath which the twyer is blowing, the latter being placed a little below the grate. A second vertically inclined grate, leaning on the former, closes the opening of the escape flue. The fuel is put on the first grate, kept back by the second one; it develops its smoke in the superior

A.D. 1856.-Nº 258.

Provisional Specification.

Descos' Improvements in Consuming Smoke.

chamber. This smoke is carried away by the current of air which escapes from the twyer in the ash box; it mixes with the atmospheric air of the same current, & passes again under the grate, where it is entirely consumed by the contact of a distilled fuel in order to escape by the flues.

LONDON : Printed by GEORGE EDWARD EYRE and WILLIAM SPOTTISWOODE, Printers to the Queen's most Excellent Majesty. 1856.