

Specification of William Louis Earle : apparatus for the combustion of smoke, &c.;

Contributors

Earle, William Louis.

Publication/Creation

London : Great Seal Patent Office, 1860 (London : George E. Eyre and William Spottiswoode)

Persistent URL

<https://wellcomecollection.org/works/xbnyk37q>

License and attribution

This work has been identified as being free of known restrictions under copyright law, including all related and neighbouring rights and is being made available under the Creative Commons, Public Domain Mark.

You can copy, modify, distribute and perform the work, even for commercial purposes, without asking permission.



Wellcome Collection
183 Euston Road
London NW1 2BE UK
T +44 (0)20 7611 8722
E library@wellcomecollection.org
<https://wellcomecollection.org>



247

A.D. 1859, 5th OCTOBER. N° 2265.

S P E C I F I C A T I O N

OF

WILLIAM LOUIS EARLE.

APPARATUS FOR THE COMBUSTION OF
SMOKE, &c.

LONDON:

PRINTED BY GEORGE E. EYRE AND WILLIAM SPOTTISWOODE,
PRINTERS TO THE QUEEN'S MOST EXCELLENT MAJESTY :

PUBLISHED AT THE GREAT SEAL PATENT OFFICE,
25, SOUTHAMPTON BUILDINGS, HOLBORN.

Price 8d.

1860.

THE UNIVERSITY OF CHICAGO

PHILOSOPHY DEPARTMENT

1950-1951

WINTER TERM

1950-1951

1950-1951

1950-1951

1950-1951

1950-1951

1950-1951

1950-1951

1950-1951



A.D. 1859, 5th OCTOBER. N^o 2265.

Apparatus for the Combustion of Smoke, &c.

(This Invention received Provisional Protection only.)

PROVISIONAL SPECIFICATION left by William Louis Earle at the Office of the Commissioners of Patents, with his Petition, on the 5th October 1859.

I, WILLIAM LOUIS EARLE, of Alfred Place, Bedford Square, in the County of Middlesex, Gentleman, do hereby declare the nature of the said Invention, for "**IMPROVEMENTS IN APPARATUS FOR PROMOTING THE COMBUSTION OF SMOKE AND GASES ARISING FROM FUEL,**" to be as follows:—

My Invention relates to improved apparatus for effecting and regulating the mixture of gases and smoke evolved in furnaces with air, in order to promote combustion, being further improvements in or modifications of that for which Provisional Protection has been granted to me, dated September 5th, 1859, No. 2026, in which the apparatus is described as being preferably of a wedge-form, with perforations emerging on the incline side. Now, I further make such mixing apparatus of any suitable form, and instead of subdividing the several films of air and smoke by numerous secondary partitions, I pass the air and smoke through the apparatus, simply in films arranged in alternate order, or they be subdivided at the surface of emergence by small partitions; instead of altogether suppressing the secondary partitions, they may be suppressed only in either the air or smoke passages, say, to admit the smoke in films, while the air passes through numerous perforations, being merely the films subdivided. In this manner I find a rectangular form of apparatus well adapted for the purpose, the smoke being allowed to pass directly from side to

Earle's Improvements in Apparatus for the Combustion of Smoke, &c.

side through narrow slit-like perforations, while the air ascends from below in films intermediate of the planes of the smoke perforations, and escaping in a direction at right angles, or otherwise, to the ingress, either in the form of films or further subdivided on emerging. According to this arrangement, I find the apparatus may be readily constructed of plates or sheets of refractory material, 5 in which the passages for the films of smoke and air may be readily formed by indentation in the sides, which plates may be placed together while still plastic, and burnt, or they may be burnt and combined afterwards, as required, and adapted for the furnace to which they are to be applied. Instead of carrying both sets of perforations through the apparatus, so that the air and smoke 10 combine only on emerging from the perforations; I sometimes increase the sectional area of the one series of passages towards the flues or combustion chamber, and admit by numerous transverse perforations the air to pass into the smoke passage, and mix therewith previous to emerging into the combustion chamber, or it may be the smoke that is admitted into the air passages. 15 By all these means I am enabled to supply air in sufficient quantities, & to intimately mix it with the smoke and gases to ensure the desired combustion.

LONDON :

Printed by GEORGE EDWARD EYRE and WILLIAM SPOTTISWOODE,
Printers to the Queen's most Excellent Majesty. 1860.